

RIDGERS



DISC RIDGER



Robust Bearings



Adjustable Spacing



Three-point Linkage

The Disc Ridger is mounted on the tractor's universal three-point linkage system and can easily be transported to the field. The Ridger offers options ranging from 1-, 2- and 3-ridges or seedbeds. Disc angles can be adjusted up to 45°. This machine is mainly used by vegetable farmers. The disc Ridger is manufactured from a 150mm x 150mm H-beam toolbar and is equipped with heavy duty flange-type bearings mounted on a 32mm hanger with a heavy duty shaft and flange.

STOCK CODE	AWB 24 / 1	AWB 24 / 2	AWB 24 / 3
TYPE	SINGLE	DOUBLE	TRIPLE
NUMBER OF DISCS	2	4	6
NUMBER OF ROWS	1	2	3
TOTAL WIDTH	1 800mm	3 050mm	4 050mm
TOTAL LENGTH	500mm	1 100mm	1 100mm
TOTAL HEIGHT	1 250mm	1 250mm	1 250mm
WORKING DEPTH	250mm	250mm	250mm
WORKING WIDTH	300 - 1 350mm	300 - 2 600mm	300 - 3 600mm
SPACE BETWEEN RIDGES	ADJUSTABLE	ADJUSTABLE	ADJUSTABLE
DISC DIAMETER	610 / 660mm	610 / 660mm	610 / 660mm
REQUIRED POWER	35 - 40kW	50 - 55kW	60 - 65kW

Manufacturer reserves the rights to change the above without any notice.