

PLOUGHS



TORPEDO DISC PLOUGH



Pipe Frame



Adjustable Discs



Rotational Movement

A pipe frame Disc Plough is manufactured from 152mm x 10mm round tubing. Models are available in 2-, 3-, 4- and 5-disc Ploughs and mounted discs have a diameter of 660mm x 6mm. These discs can be adjusted according to soil conditions by position and direction angle. Disc Ploughs have a rotational movement of the disc. Round frame Disc Ploughs are used for cultivation of stubble and raw lands.

STOCK CODE	SKTLP 2	SKTLP 3	SKTLP 4	SKTLP 5
TYPE	2 DISC	3 DISC	4 DISC	5 DISC
WORKING DEPTH	200 - 300mm	200 - 300mm	200 - 300mm	200 - 300mm
GROUND CLEARANCE	700mm	700mm	700mm	700mm
WORKING WIDTH	660mm	990mm	1 320mm	1 650mm
SPACE BETWEEN DISCS	530mm	530mm	530mm	530mm
DIAMETER OF DISC	660mm	660mm	660mm	660mm
VERTICAL DISC ADJUSTMENT	15" / 18" / 22"	15" / 18" / 22"	15" / 18" / 22"	15" / 18" / 22"
REQUIRED POWER	30kW	45kW	60kW	75kW
WEIGHT	270kg	410kg	580kg	750kg

Manufacturer reserves the rights to change the above without any notice.