

# CULTIVATORS



## VIBROFLEX TILLER - DEPTH CONTROL WHEELS



**Vibrating Effect**



**Hydraulic Folding**



**Spring-loaded Tines**

The vibroflex tiller series is mounted on the three-point linkage of the tractor. The optimum operating speed is 12 kilometers per hour for the necessary vibrating effect to ensure maximum efficiency. The vibroflex tiller is used for weeding, cultivation of soil and seedbed preparation. Advantages of the vibroflex include: soil can be worked and reconsolidated in one pass, optimum seedbed preparation, loosens top layer of soil to allow faster germination and enhanced plant growth.

STOCK CODE	AVBTH 3 / 25	AVBTH 3 / 33
FRAME	TRIPLE BEAM	TRIPLE BEAM
NUMBER OF TINES	25	33
TOTAL WIDTH	6 000mm	8 000mm
WORKING DEPTH	50 - 150mm	50 - 150mm
DEPTH CONTROL WHEELS	STANDARD	STANDARD
WORKING WIDTH	5 750mm	7 750mm
SPACE BETWEEN TINES	250mm (ADJUSTABLE)	250mm (ADJUSTABLE)
TINE LENGTH	650mm	650mm
REQUIRED POWER	125 - 140kW	165 - 180kW

*Manufacturer reserves the rights to change the above without any notice.*