

# SPREADERS



## PS-13T MULTI-PURPOSE SPREADER



**ISO Bus System**



**Highly Economical**



**Effective Spreading**

The PS-13T spreader is a revolutionary addition to the already successful BPI range of spreaders. The PS-13T spreader is equipped with an ISO Bus precision system and handles with ease in extreme conditions. PS-13T's unique design enables it to spread widths from 12m to 30m depending on material density. The chassis is designed to handle weights of up to 20ton with ease with a J2 suspension that completely disassembles compaction of material inside the loading space and the oil demand is minimal, as little as 90L / min.

STOCK CODE	PS-13T
MAXIMUM LOAD CAPACITY	20 TON (13 TON/ LIME, DENSITY LEVEL- 1.2TON/M <sup>3</sup> )
CUBIC METER CAPACITY	10.8m <sup>3</sup>
TOTAL BIN LENGTH	5 330mm
TOTAL BIN WIDTH	2 200mm
TOTAL SPREADER LENGHT	7 800mm
OVERALL HEIGHT	2 440mm
GROUND CLEARANCE TO AXLE	500mm
GROUND CLEARANCE TO SPINNER	800mm
DISCHARGE RATE PER/HA	30kg - 3 000kg
SPREADING WIDTH	12 000 - 13 000mm
OPTIMUM HYDRAULIC OIL FLOW	85 - 100ℓ/min
TYRE SIZE	500/60 - 22.5"
REQUIRED POWER	130KW - above
PRECISION EQUIPMENT	ISO-BUS kit (Trimble) installed/ standard

*Manufacturer reserves the rights to change the above without any notice.*